



Vanguard® Flashhead Cables

Flash Technology offers three shielded cables for use with Vanguard lighting systems, based on the final structure height. Each has the characteristics and construction outlined below, while variances and part numbers can be found on the reverse.

Specifications

- Temperature rating: -40°C to +90°C dry, +75°C wet
- Cold bend at -40°C
- Voltage rating: 600V RMS
- RoHS compliant
- UL type tray cable (type TC rated)

Construction

- Shield: Aluminum mylar shield
- Jacket: Direct burial, sunlight (UV) resistant, ozone resistant, flame retardant, excellent moisture resistance



Vanguard® Flashhead Cables

10 AWG 2/C Cable

- Part number: 4210000
- Overall diameter: 0.43" nominal
- Weight: 161 lbs/1000 ft
- Cable length: Less than 375', available in 25' increments

ITEM NUMBER	SIZE	INSULATION COLOR
1	10 AWG	Black
2	10 AWG	Red
3	10 AWG	Drain

8 AWG 2/C Cable

- Part number: 4370000
- Overall diameter: 0.565" nominal
- Weight: 236 lbs/1000 ft
- Cable length: 376-600', available in 25' increments

ITEM NUMBER	SIZE	INSULATION COLOR
1	8 AWG	Black
2	8 AWG	Red
3	10 AWG	Drain

6 AWG 2/C Cable

- Part number: 4206000
- Overall diameter: 0.691" nominal
- Weight: 323 lbs/1000 ft
- Cable length: 601-850', available in 100' increments

ITEM NUMBER	SIZE	INSULATION COLOR
1	6 AWG	Black
2	6 AWG	Red
3	10 AWG	Drain

